

AIRCOLOR MATT & SATIN BLACK



VERSION: 140228 Page:1/2

ACRYLIC ENAMEL

DEFINITION

AIRCOLOR MATT & SATIN BLACK is a premium acrylic enamel with especially formulated for the quick coating of Industrial surfaces. Thanks to the atomization it can also be used in larger surfaces. An extreme high content of pigments and specific additives provide excellent opacity, high film-thickness, low tendency for runs and good adhesion direct on metal. It can be applied either for spot repairs or refinishing parts.

PHYSICAL CHARACTERISTICS

Nature:	Acrylic
Colour:	Black
Aspect:	Satin (Gloss: 50% at 60º)
-	Matt (Gloss: 10% at 60%)
Specific weight:	0,8 kg/l at 20°C
Propellant:	GLP
Aerosol pressure:	4 bar at 20⁰C
Yield:	Depending on consistence
	and colour of the substrate:
	400 ml are sufficient for approx.0,8 - 1,0 m ²
Temperature resistance:	to 90°C

Temperature resistance: to 90°C

SURFACE PREPARATION

PROCESS		Paint OEM	Primer
	P360	\checkmark	\checkmark
	DA93	\checkmark	\checkmark

APPLICATION METHOD

Į,			<u>}</u>
2'	20-25 cm	2-3 coats	5'

DRYING TIMES

20ºC	10'	30'

AIRCOLOR MATT & SATIN BLACK

ACRYLIC ENAMEL



REMARKS

Shake the aerosol before use for 2 minutes after hearing the sound of the steel mixing balls. Protect the areas that do not need to be painted. Drying time depends on temperature, humidity and film thickness which has been applied.

EQUIPMENT CLEANING



SAFETY

Follow instructions on the product label. For more information check the Safety Data Sheet. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between $+5^{\circ}$ C and $+30^{\circ}$ C.

GUARANTEE

In unopened original packaging, one year from manufacturing date.

For any technical information contact with our Customer Attention Service or our Technical Department. ROBERLO SA declines any responsibility due to an incorrect use of the product.